

1. PRODUCT NAME

Quartz Slab

2. MANUFACTURER

OCEANIC 6 SOLUTIONZ
4TH FLOOR, PLOT NO. 01
BLOCK A HSIIDC PARK
SECTOR 22 PANCHKULA
HARYANA 134109

+91 98101 13016

sales@oceanic6.com

www.oceanic6solutionz.com

3. PRODUCT DESCRIPTION

Basic Use: Quartz is a man-made substance that has been manufactured to seem like a number of natural goods, including marble and granite, which have dramatic veining and shine, and travertine, which has delicate swirling swirls. Whether you're looking for quartz counter tops for your kitchen or bathroom, it's a counter top material that will make you feel pleased no matter what.

Quartz counter tops are not difficult to maintain; in fact, they require very little upkeep. If you want to keep your kitchen counters looking their best, proper care and upkeep are crucial!

Slab Size: 3200 x 1600mm & 3550 x 2000mm.

Slab Thickness: 2cm and 3cm (+, -1.5mm)

Weight: Quartz weight approximately per sqft.

Thickness 2cm: 5kg/sqft. or 11 lbs/sqft.

Thickness 3cm: 6kg/sqft. or 13 lbs/sqft.

Top Surface Finish: Leather, Flamed, Brushed, Polished, Honed, Lapatura.

Custom finishes available upon request.

Color Ranges:

Calacatta Tornado	Calacatta (Calcutta Spider)
Calacatta Almond	Calacatta (Wonder)
Calacatta California Black	Calacatta (Forest Grey)
Calacatta Gold	Calacatta (Leon)
Calacatta Loria	Calacatta (Green Lily)
Calacatta Royal	Calacatta (Victoria Green)
Calacatta Extreme	Calacatta (Calcutta Hadal)
Calacatta Venatino	Calacatta (Venato Green)
Calacatta Sepia	Calacatta (Swiss White)
Everest Carrara	Calacatta (Calcutta River)
Frost White	Calacatta (Evoque White)
Ice White	Calacatta (Carrara King)
Sparkle White	Calacatta (Forest Gold)
Super White	Calacatta (Calcutta Loria)
Nero Marquina	Calacatta (Lapis Azuli)
Metropolitan	Calacatta (Calcutta Gold)
Sandy Wood	Calacatta (Carrara Blue)
Forest Grey	
Indiana White	
Plato	

Thicker slabs available upon request.

Note: Due to printing process, the colour of the actual products may differ from the picture. For true colour matching purposes refer the sample.



Technical Information: Standard Specification selection criteria for Slabs.

TEST SPECIFICATION	STANDARD OF TEST	STANDARD OF MEASUREMENT	RANGE OF QUARTZ
Water Absorption	EN 14617 1	%	<0.1
Thermal Expansion Linear Coefficient Of T.e.	EN 14617 - 11	10-6 /°C	<30
Surface Hardness	EN 101	Moh's Scale	6 7
Density	EN 14617 1	gm / cc	>2.30
Compressive Strength	EN 14617 15	Mpa	170 - 250
Flexural Strength / Module	EN 14617 2	Mpa	27 60
Glossiness	Reflection	%	>55
Chemical Resistance (Resistance to acid)	EN 14617 10	Cl.C4	C1.C4
Resistance To Fire	DIN 4102		bl
Shock Resistance	ASTM C848		No Scaling
Slippage Resistance	DIN 51130	Joule	Levigato 320 = R9Honed 320 = R9Geschliffe 320 = R9
Resistance To De-Icing Salts	ASTM C672		120 180
Resistance To Rapid Freezing & Thawing	"ASTM C666 DIN 52104"		Levigato 320 = R9Honed 320 = R9 Geschliffen 320 = R9
Impact Resistance	ASTM C1709		5. + / -2
Abrasion Resistance	EN 14617- 4	mm	172 25

4. INSTALLATION

Anchoring: Depending upon product usage, mechanical anchors are available.

5. AVAILABILITY AND COST

Contact oceanic 6 solutionz for inventory availability.

6. MAINTENANCE

Granite is easy to care for. Clean with mild soap and water. For stain prevention and removal, contact a stone care company. Information about such companies is available through oceanic6solutionz.

Note: Due to printing process, the colour of the actual products may differ from the picture. For true colour matching purposes refer the sample.

